

iluminar

WL220-PoE Series

Product Features

- White light illuminator designed to provide dedicated lighting for IP cameras via PoE+ (Power over Ethernet) enabled network infrastructure
- IEEE802.3at Compliant
- SMT LED technology
- Distances up to 220' (67m)
- Angles 10°, 30°, 60°, 100° & 120°
- IP67 weatherproof
- Built-in photocell light on/off
- Photocell following contact
- Telemetry input for remote switching



**PoE+
Powered**

Who are Iluminar?

Iluminar (which stands for "illuminate" in Spanish) are a specialist manufacturer and supplier of IR and white light illuminators and license plate recognition products. The owners have over 30 years combined industry experience. Our company mission is to supply high quality and reliable lighting and license plate recognition products to the CCTV industry, backed by unsurpassed customer service.

What is White Light?

White light is visible light. Visible light is advantageous in that it acts as a deterrent as well as providing additional lighting for color cameras.

All Iluminar's white light illuminators are designed to provide superior visible lighting for CCTV systems. They are available with a range of angles to cover different ranges and scenes.

Supplied with an IP67 rating, they are vandal proof and can be used outdoors. The hardened housing provides protection from the harshest weather conditions and rapid temperature variations (-58°F to 140°F).

All Iluminar illuminators have a built-in photocell and are supplied with a wall mounting bracket. They are all low powered with both 12Vdc and 24VAC models available, removing the requirement for additional power supplies as with other illuminators.

Models

Model Number	Angle	Distance		HOV	
WL220-10-PoE	10°	220'	67m	38'	12m
WL220-30-PoE	30°	115'	35m	62'	19m
WL220-60-PoE	60°	82'	25m	95'	29m
WL220-100-PoE	100° x 50°	55'	17m	133'	41m
WL220-120-PoE	120°	46'	14m	159'	48m

General

Electronics	High efficiency surface mount high power LED's with advanced current limited integral control circuitry
Number of SMT LED's	16
Construction	Robust high quality aluminum extrusion
Front window	Polycarbonate high transmittance protective (vandal-proof) clear
Finish	Silver anodized
Power cable/connector	IP67 rated RJ45 Cat5e compliant connector
Interface Connector	Photocell following contact & remote telemetry input
Pressure Equalization Vent	Prevents thermal expansion & pressure cycling
Photocell	Adjustment via pot
Illumination	Adjustable via pot
Operating Temperature	-58° to 140°F (-50° to 60°C)
Weight	2.3lbs (1.05Kg)
Dimensions	4.49" x 4.33" x 3.07" (114 x 110 x 78mm)
Mount	Silver powder coated stainless steel wall mount. Adjustable via M6 Allen key (included)

Electrical

Power over Ethernet (PoE)	IEEE802.3at compliant
Consumption	26W

Lighting Output

Lumen Output	928lm
Wavelength	Visible Spectrum (400-750nm)
Color Temperature	6500K
Color Rendering Index (CRI)	74-80+

Certifications

Safety	EN60598:2004 EN60825-1	Electrical Safety Laser Eye Safety
IP	IP67 in accordance with EN60529:1992	
EMC	EN61000, FCC part 15.107 15.108 Class B	
WEEE	Waste Electrical & Electronic Equipment European directive 202/96/EC	
RoHS	Restriction of Hazardous Substances European directive 202/95/EC	