

# *iluminar*

Below are some highlights of Iluminar products vs. our competition.

- Iluminar units are anodized aluminum instead of painted. Painted units insulate the heat sink; therefore, the units will run hot.
- Iluminar units have a pressurized equalization vent fitted as standard. This vent allows moisture trapped inside to escape, as well as, prevents seals from rupturing due to changes in pressure.
- Iluminar units have interface connector as standard.
- Iluminar uses a high quality polycarbonate lens that allows 90% transmission vs. 80%.
- Iluminar units provide power and photocell sensitivity on the side of the units instead of on the back. This makes it easy for the installer to adjust after installation instead of having to uninstall the unit.
- Iluminar units have the photocell mounted on top instead of the back of the unit. Photocell on the back of the unit causes the unit to come on at earlier times due to shadows and therefore wastes energy and life of the illuminator.
- Iluminar units have more LED's so our units can provide better distances.
- Iluminar units are IP67 rated, including Iluminar IP units, vs. IP66.
- Iluminar IP units are the most powerful IP units on the market.
- Iluminar provides the largest selection of low voltage lighting in the industry.
- Iluminar has the best lead times of any CCTV lighting company in the industry.
- Iluminar is the only CCTV lighting company based in the United States.
- Iluminar provides superior support and customer service.
- Iluminar is always willing to go out and meet with staff and clients for training and education
- Iluminar owners are former owners of another UK based CCTV Lighting manufacturer

Iluminar Inc, 16107 Kensington Drive #124, Sugar Land, Texas 77479  
+1-281-438-3500 phone +1-281-835-5777 fax  
[www.iluminarinc.com](http://www.iluminarinc.com)